

revolution

R10


Two - Post Lift / 10,000 lbs. capacity

FEATURES:

- 3-stage front and 2-stage rear arms enable greater pickup point access
- Direct pull lifting technology - full stroke hydraulic cylinders in each column
- Top mounted pull design cylinder protects piston inside of carriage
- Overhead cable for equalization
- Spring operated arm restraints, disengage at floor level
- Padded overhead switch bar
- Single point lock release
- Large rubber-padded swivel adapters with extra height extensions are standard

Low-Profile Adapter Design

The R10 features low-profile, oversized pads with extensions to raise most vehicles on the road today. Includes four (each) adapter extensions at 3.5" and 5" (89mm, 127mm) and (1) column storage bracket.



Gold Certified

Revolution's R10 is ALI Certified. The R10 lift meets the highest industry safety and performance standards. Look for the Gold label.

Specifications	R10
Capacity	10,000 lbs. (4535kg)
Rise	71 -1/8" (1806mm)
Maximum Rise	76 -1/8" (1934mm) with 5" extension
Overall Height	143" (3632mm)
Overall Width	131" or optional 137" (3327-4380mm)
Drive Through Clearance	99" or optional 105" (2515-2667mm)
Overhead Switch Height	137-1/4" (3486mm)
Front Reach (Min./Max.)	24-1/2" / 44-3/8" (621mm /1127mm)
Rear Reach (Min./Max.)	36" / 58" (914mm /1473mm)
Min./Max. Adapter Height	3-5/8" (219mm) w/ no adapter extension 8-5/8" (792mm) w/ 5" adapter extension
Width Inside Column	109" or (optional 115" (2769mm/2921mm)
Voltage/Amps	208/230, 15 amps; 208/230, 16 amps
Motor/Phase*	1ph/2HP/50Hz; 1ph/2HP/60Hz
Ceiling Height Required	144" (3658mm)

*Optional 3-phase available.



Model Shown:
R10N100
10,000 lbs. capacity



revolution

www.revolutionlift.com

- 2700 Lanier Drive Madison, IN 47250
- phone: 812.273.1622 ■ sales@revolutionlift.com



Lit# REVOLUTION R10_R12 cutsheet_2016.01

©2016 Vehicle Service Group™. Printed in the U.S.A., All Rights Reserved.

Unless otherwise indicated, Revolution Lift®, Vehicle Service Group™, DOVER and all other trademarks are property of Dover Corporation and its affiliates.

revolution

R12

Two - Post Lift / 12,000 lbs. capacity

FEATURES:

- 2-stage front and rear arms
- Two full-stroke cylinders with overhead cable for equalization
- Spring operated arm restraints, disengage at floor level
- Adjustable overhead heights available*
- Adjustable width and drive-thru settings
- Padded overhead switch bar
- Single point lock release
- Large frame-engaging swivel adapters with extra height extensions are standard
- Durable powder coat finish

Low-Profile Adapter Design

The R12 features low-profile, oversized pads with extensions to raise most vehicles on the road today. Includes four (each) adapter extensions at 3.5" and 5" (89mm, 127mm) - includes column storage bracket.



Specifications	R12
Capacity	12,000 lbs. (5443kg)
Rise	72 -3/4" (1848mm)
Maximum Rise	77-3/4" (1975mm) With 5" adapter extension
Adjustable Overall Height Options	166" (4216mm) Standard Height 178" (4521mm) Extended Max. Height* 154" (3912mm) LH1 143" (3632mm) DP
Overall Width	140" or optional 146" (3556 / 3708mm)
Drive Through Clearance	102-3/4" or optional 108-3/4" (2609 / 2762mm)
Overhead Switch Height Options	160-1/8" (4067mm) Standard 172-1/8" (4524mm) Extended* 148-1/8" (3762mm) LH1 137-1/8" (3483mm) DP
Front Reach (Min./Max.)	35" / 54" (889 / 1372mm)
Rear Reach (Min./Max.)	35" / 54" (889 / 1372mm)
Min./Max. Adapter Height	4-3/4" (120) w/ no adapter extension 9-3/4" (248mm) w/ 5" adapter extension
Width Inside Column	120-7/8" (3070mm) Standard 114-7/8" (2918) Optional
Voltage/Amps	208/230, 12 amps; 208/230, 16 amps
Motor/Phase**	1ph**/2HP/50Hz; 1ph**/2HP/60Hz
Ceiling Height Required	168" (4267mm)

*Hose and cable kit required **Optional 3-phase available



Model Shown:
R12N200
12,000 lbs. capacity

Gold Certified

Revolution's R12 is ALI Certified. The R12 lift meets the highest industry safety and performance standards. Look for the Gold label.

revolution
www.revolutionlift.com

- 2700 Lanier Drive Madison, IN 47250
- phone: 812.273.1622 ■ sales@revolutionlift.com