

# revolution

# RTP9

*Two-Post Lift / 9,000 lbs. capacity*

## RTP9 FEATURES:

- Commercial grade lift - designed for facilities with low ceilings
- Dual hydraulic cylinders with chain
- 2-stage symmetric arms
- Carriage latch system – engages every 3" (76mm)
- Secondary lock system includes a spring actuated slack chain locking device
- Adapter extensions included
- Includes four (4) frame-engaging truck adapters



Shown: RTP9N000MBL  
9,000 lbs. (4082kg) capacity


### Gold Certified

Revolution's RTP9 is ALI Certified. This lift meets the highest industry safety and performance standards. Look for the Gold label.



### Low-Profile Adapter Design

The RTP9 features low-profile, oversized pads with extensions to raise most vehicles on the road today. Includes four (each) adapter extensions at 3.5" and 5" (89mm, 127mm) and (1) column storage bracket.



Specifications	RTP9
Capacity	9,000 lbs. (4082kg)
Rise With Adapter Extensions	80-1/2" (2045mm)
Rise Without Adapter Extensions	72" (1829mm)
Overall Height	111-1/4" (2826mm)
Overall Width	138-1/2" (3518mm)
Drive Through Clearance	97-1/4" (2470mm)
Width Inside Column	111" (2819mm)
Arm Reach (Min./Max.)	30" / 46-1/4" (762mm / 1175mm)
Minimum Adapter Height	3-1/2" (89mm)
Drive-Over Height	1-1/2" (38mm)
Voltage/Amps	208/230 / 18.7 amps
Motor/Phase	1ph*/2HP/50Hz 1ph*/2HP/60Hz
Minimum Ceiling Height	113" (9'-5") (2870mm)

\*Optional 3-phase available. Lift color is blue.

**revolution**  
[www.revolutionlift.com](http://www.revolutionlift.com)

- 2700 Lanier Drive Madison, IN 47250
- phone: 812.273.1622 ■ [sales@revolutionlift.com](mailto:sales@revolutionlift.com)



Lit# REVOLUTION RTP9 cutsheet\_2016.01

©2016 Vehicle Service Group™. Printed in the U.S.A., All Rights Reserved. Unless otherwise indicated, Revolution Lift®, Vehicle Service Group™, DOVER and all other trademarks are property of Dover Corporation and its affiliates.