OPTIONAL LIFT ACCESSORIES kotary)

Increase bay productivity with these commonly used two-post lift accessories

Adapter and Mounting Rack

Required for raising minivans with running boards. Includes four adapters, mounting rack and hardware.

- Adjustable range provides 4 7/8" (124mm) to 6 3/4" (171mm) additional height
- Capacity 1,750 lbs. (794k) per adapter Rubber contact surface protects
- undercoated surfaces

Auxiliary Adapters

Auxiliary adapters for use when raising certain vans or pickups. Includes four adapters, mounting rack and hardware.

- 2,500 lbs. (1134kg) capacity per adapter
- Adds 14 3/8" to 17 3/8" of additional overall adapter height (365 - 441mm)



#FJ6195YL Adds 12 3/8" (314mm) of height - includes 2 adapters

#FJ6137BK

Extended Height Adapter

Required to lift 1988 or newer General Motors[®] GMT400 pickup trucks. Includes four adapters, mounting rack and hardware.

- Capacity 2,500 lbs. (1134kg) maximum per adapter
- Maximum overall height: 14" (356mm)

#FJ6133BK

#FJ6100BK

Consult your Rotary Authorized Distributor for more information concerning these accessory options.

Polymer Pad Adapter Kits

Polymer pad adapters for use with new car undercoating. Includes four adapters, mounting rack and hardware. 2,500 lbs. (1134kg) capacity per adapter

Rubber contact surface protects undercoated surfaces



Adapters and Organizer Rack

Accommodate more vehicles quickly and easily with more adapters plus keep them organized

- Four FJ696, four FJ697 and four FJ698 adapters
- Two piece column or wall-mounted adapter organizer rack (FJ6108)

Also available in different configurations. CONSULT FACTORY FOR OPTIONS

Thread-Up Adapter

Auxiliary adjustable thread-up adapter with rubber pads allow for protection of underbody vehicle components or undercoating. For raising certain vans or pickups.

#FJ6197 (for 10,000 lbs. (4536kg) capacity lifts includes (4) FJ6214 adapters) Required use on 3-stage arms when lifting trucks and other frame vehicles

RA Adapter

Set of four (4) FJ6202 polymer pad round adapters. Adapters thread-up to allow protection of the vehicle underbody components or undercoating for no metal to metal contact. For use on 3-stage arms when lifting uni-body construction



vehicles. Also available for use with stackable inserts.

Adapter Extensions

Provides additional lifting height when vehicles require additional clearance or use on front or rear to level vehicle on lift. Fits models SPO/SPOA10 RA/TA and SP012TA 3-stage arms

Includes four 3 1/2" (89mm) and

four 5" (127mm) adapter extensions, mounting rack and hardware.

Air / Utility Box

Mounts easily on any column and provides quick access to utilities

- Two 110v electric outlets and air connection
- The filter/regulator/lubricator helps extend the life of your air tools

#FA5911BK

Tool Holder

To keep tools handy for the technician, this patented tool holder keeps air guns, torque sticks, and other tools within easy reach. This accessory mounts easily in holes already drilled and tapped in the two-post column.



Extended Height Kits Raise the overhead clearance on

10,000 and 12,000 lbs. capacity two-post lifts to service more vehicles at a comfortable working height. Kit includes column extensions and hardware.

CONSULT FACTORY FOR OPTIONS

Accessories shown may be used with most frame contact models. Adapters fit any surface mounted, frame engaging Rotary Lift manufactured since October of 1973.



Jack Stands

The RS4, 4,000 lbs. capacity jack stand provides supplemental assurance of vehicle lift safety. Maximum height: 84" (2133mm)

Minimum height: 55 1/2" (1410mm) Fine thread-up height: 1 5/8" to 7 1/8" (41mm to 181mm)



#MW-200

MW-200 Tire Lift

200 lbs. capacity air operated tire and wheel lift. Provides maneuverability and adjustable lifting and lowering speeds.

- Quick transfers to tire balancers
- · Easy positioning of the tire / wheel
- Includes air hose and auxiliary air tool connection

#MW-500

500 lbs. capacity model available

Wheel Wing[™] Kit Tire Arm

Handy for tire rotations and brake jobs, the Wheel Wing mounts easily on any column arm and holds a tire at lift arm height. Folds away when not in use.

- · Adjustable to fit various lift arms
- Includes set of 2 arms, 2 magnetic lug nut dishes, shims

#FA5974

Door Defender

The door defender is a low profile solid rubber guard designed to fit over the two-post lift carriage. Allows technicians to easily enter and exit the vehicle without vehicle damage. #N823 Includes one (1) padded defender, and adhesive.



Column Base Plate Cover

Refresh your shop's appearance with a unique accessory from Rotary Lift designed to cover the base plates on popular two-post lift models. Keep mounting hardware hidden and safely enclosed and #N539 protected from day to day use. Base plate covers fit standard Rotary Lift SPOA10, SPOA9 (200 series and above) and SPOA7 (200 series and above) lifts.







adapter extension kit

















OPTIONAL LIFT ACCESSORIES

Lock Light™

Provides an instant green light visual confirmation when lift is lowered to its locks. Compatible with most surface and high-pressure lifts that use an electric/hydraulic power unit providing an unused pressure port is available. Kit includes:

Kotary

- Indicator light assembly
- Pressure switch
- Mounting bracket
- 10' of electrical wire

#FA834 / 110V #FA835 / 220V

TECH LIGHT[™] Line Light 2

Attach the 2 ultra slim light wands to colums for effective, efficient 2-post lighting where you need it. Supplied with 4 magnetic clips for

- easy positioning. Includes: • (2) 96 LED lights with 25' of
 - cable and 20W power supply3" spiral cords stretches to
 - 16" for placement under vehicle
 - Magnetic junction box
 - Input voltage 100-240 V AC


#FA5701

TECH LIGHT™ Line Light R

Rechargable LED inspection hand lamp with top spot light.Supplied with flexible suspension clips holder with both hook and magnet for positioning the light exactly where you need it

Additional suspension solutions available as accessories.

- 180 lumen in main light operates for up to 3 hours
- 120 lumen in spot light operates for up to 6 hours
- 4 hour charging time



TWO-POST STANDARD / OPTIONAL LIFT FEATURES

FEATURE Standard Feature Optional Feature Optional Feature	AT07 7,000 lbs.	SPOA7 7,000 lbs.	SP010 10,000 lbs.	SPOA10 10,000 lbs.	SP012 12,000 lbs.	SP015 15,000 lbs.	SP018 18,000 lbs.
Lift column design	Asymmetric	Asymmetric	Symmetric	Asymmetric	Symmetric	Symmetric	Symmetric
ALI Certified	•	•	•	•	•	•	•
Surface mounted models	•	•	•	•	•	•	
SHOCKWAVE™ Equipped models	N/A	0	0	0	0	N/A	N/A
3-phase power units	0	0	0	0	0	0	0
Single point air operated lock release	•	•	•	•	•	•	•
Multi-position locking systems	•	•	•	•	•	•	•
Standard single piece "Double S" column construction	•	•	•	•	•	•	•
Hydraulic cylinders in each column	•	•	•	•	•	•	•
Overhead cables / clear floor design	•	•	•	•	•	•	
Seismic rated column baseplate	N/A	0	0	0	N/A	N/A	N/A
Adjustable narrow column width	N/A	N/A	0	0	N/A	N/A	N/A
Adjustable wider column width	N/A	N/A	N/A	N/A	0	N/A	N/A
Extended higher rise option	N/A	N/A	0	0	0	N/A	N/A
Extended overhead height options	N/A	N/A	0	0	0	N/A	N/A
Low ceiling model available	N/A	N/A	N/A	N/A	0	0	0
3-stage arms	N/A	N/A	0	0	0	N/A	N/A
Automatic arm restraints	•	•	•	•	•	•	•
Overhead padded switch bar	•	•	•	•	•	•	•
3 position wheel spotting dish	•	•	•	•	•	•	•