

Available with SHOCKWAVE™



SPOA7-LPA Two Post Lifts

7,000 lbs. CAPACITY Low Profile Arm Lifts



Model shown:
SPOA7X5LX

Lift shown with optional accessories

ALI Gold Certified 2-Post Lift

***Low-profile, two-stage arms with thread-up, round adapters
- designed to lift low-profile vehicles and more!***

True asymmetric column design with adjustable lift height options

The World's Most Trusted Lift™

www.rotarylift.com

SPOA7-LPA Two-Post Lifts

SPOA7-LPA 2-stage low profile arms with round RA adapters reach a variety vehicles with ease.

Round polymer adapters come standard with asymmetric lift models that thread-up or have optional stackable inserts creating greater lifting options. No metal to metal contact.



SPOA7 LOW PROFILE ARM

The low profile, 2-stage arm is slimmer with a wider stance, creating additional clearance to accommodate a variety of vehicle models.



Shorter arm gusset for greater clearance

Minimum arm reach and overall arm sweep means technicians have the ability to precisely spot and lift unibody sport and compact profile vehicle designs.

Optional Accessories

Wheel Wing™ Tire Arm

100 lbs. capacity Wheel Wing tire arm mounts easily on any column arm and holds a tire at lift arm height. Folds away when not in use and includes set of 2 arms, 2 magnetic lug nut dishes



#FA5974

Air / Utility Box

Mounts easily on any column and provides quick access to utilities. The filter/regulator/lubricator helps extend the life of your air tools. Includes two 110v electric outlets and air connection



#FA5911BK

Tool Holder

This patented tool holder keeps air guns, torque sticks, and other tools within easy reach. Mounts easily in provided holes in the two-post column.



#FA5919BK

Jack Stands 4,000 lbs. capacity

The lift certified RS4 jack stand provides added assurance of vehicle lift safety.

Maximum height: 84" (2133mm)

Minimum height: 55 1/2" (1410mm)

Fine thread-up height: 1 5/8" to 7 1/8" (41mm to 181mm)

#RS4



Adapter Extensions

Provides additional lifting height when vehicles require additional clearance or use on front or rear to level vehicle on lift.

Kit #FJ7880BK

Includes four 3 1/2" (89mm) and four 5" (127mm)

adapter extensions, mounting rack and hardware.



TECH LIGHT™ Line Light 2

Attach the 2 ultra slim light wands to columns for effective, efficient 2-post lighting where you need it. Includes magnetic clips for easy positioning.

- (2) 96 LED lights with 25' of cable and 20W power supply
- 3" spiral cords - stretches to 16" for placement under vehicle
- Magnetic junction box
- Input voltage 100-240 V AC



#FA5701

MW-200 Tire Lift

200 lbs. capacity air operated tire and wheel lift. Provides maneuverability and adjustable lifting and lowering speeds. Air hose and auxiliary air tool connection included.





#MW-200

SPECIFICATIONS

Available with SHOCKWAVE™



Model	SPOA7-LPA SPOA7LPA SW
Capacity	7,000 lbs. (3175kg)
Rise*	71 3/8" - 73 3/8" (1813 - 1864mm)
A. WITH SHOCKWAVE	74 3/8" - 76 5/8" (1889 - 1946mm)
B. Height Overall**	11' 8 1/2" (3569mm)
C. Width Overall** (outside of base plate)	11' 5 3/8" (3489mm)
D. Drive-Thru Clearance	95 1/4" (2416mm)
E. Floor To Overhead Switch	11' 2 3/4" (3423mm)
F. Reach (front arm min.)	23 1/4" (590mm)
G. Reach (front arm max.)	33 1/2" (851mm)
H. Reach (rear arm min.)	33 1/2" (851mm)
I. Reach (rear arm max.)	54 3/4" (1391mm)
J. Min. Adapter Height	3 3/8" (86mm)
K. Max. Adapter Height	5 5/8" (143mm)
L. Cylinder Height	11' 10 1/2" (3619mm)
WITH SHOCKWAVE	12' 4 1/2" (3772mm)
M. Inside Columns	107 1/4" (2727mm)
Motor / Voltage 1Ø***	2 HP / 208v-230v
WITH SHOCKWAVE	5 HP / 110v
Time of Full Rise / Descent	45 / 40 seconds
WITH SHOCKWAVE	25 / 19 seconds
Ceiling Height Required:	12' (3658mm)
WITH SHOCKWAVE	12' 6" (3810mm)
Min. Bay Size	12' x 24' (3658 x 7315mm)



* Rise measures lowest or highest position of the supplied adapters from floor to full cylinder stroke.

** Overall heights and widths reflect standard settings. Alternate settings may be available, refer to Installation Instruction Manual or consult factory for details.

***Optional 3-phase electrical available.



Rotary Lift

2700 Lanier Drive
Madison, IN 47250, USA



North / South America Contact Information

Sales: p 800.640.5438
e userlink@rotarylif.com
Tech. Support: p 800.445.5438
e techlink@rotarylif.com

Global Contact Information

USA: 1.812.273.1622
Canada: 1.905.812.9920
Latin America / Caribbean: 1.812.273.1622
Brazil: +55.11.4534.1995

Assistance for Government Purchasing

Government Sales: 800.445.5438 X5655

For additional world wide contact information and a complete guide to our product offering, visit us on the web at rotarylif.com.



Contract No. 061015-RRL



Lit# SPOA7LP_Cutsheet_2016.07

©2016 VEHICLE SERVICE GROUP™, Printed in U.S.A., All Rights Reserved. Unless otherwise indicated, ROTARY LIFT, VEHICLE SERVICE GROUP™, DOVER and all other trademarks are property of Dover Corporation and its affiliates.