

Alignment Scissor Lift FMS40AL



Descriptions

01

Recessed installation allows for an unobstructed floor.



02

Recessed pockets will accommodate a large number of common turn tables.



03

Alignment kit accommodates a great wheelbase range for wheel alignments.



04

Lifting table enables flexible pick-up of vehicles for tire and chassis maintenance.



05

Positive engagement locking system ensures safety.



06

Control panel is easy to operate.



Features

- 4000kg capacity;
- Open scissor design saves space and provides greater technician access with ture vertical lifting;
- Mechanical safety locks offer maximum technician safety;
- Reliable, high quality composite bearings provide maintenace-free operation.



| - | 4800 | | - |
|---------|------|------------------------------|--------|
| 2081684 | 145 | 45-1945 1400 70 315 31 | 80 400 |
| | 550 | 550 | |
| | 5280 | | - |
| \o\ | | 20. | |

| Specifications | | | | |
|------------------------|--------------|--|--|--|
| Model | FMS40AL | | | |
| Capacity | 4000 kg | | | |
| Lifting Height | 1850 mm | | | |
| Lifting Table Capacity | 3000 kg | | | |
| Lifting Table Height | 450 mm | | | |
| Min Height | 330 mm | | | |
| Overall Length | 5280 mm | | | |
| Overall Width | 2040 mm | | | |
| Platform Length | 4800 mm | | | |
| Platform Width | 610 mm | | | |
| Lifting Table Length | 1545~1945 mm | | | |
| Motor | 2.2 kW | | | |
| Voltage | 380V/50Hz | | | |
| Air Pressure | 6∼8 Bar | | | |