

ENGINEERED TO PERFORM. BUILT TO LAST.

Reliable lift systems for independent repair shops, car dealerships, bodyshops, home enthusiasts, and heavy-duty truck facilities.

Heavy duty capacity to handle vehicles with wheelbases up to 215"





Two model lengths configured for vehicles with longer wheelbases Designed with oversized slip plates and adjustable radius gauge pockets

15

- Tall column design adds 80 3/4" rise height
- Full width slip plate allows for four wheel alignments up to 157"
- · Heavy duty high-performance cable and sheaves system
- Easy to use single point lift operation with air operated lock release
- Multi-position lock components allow lift to be level at any lock position
- · Self-chocking 41" approach ramps with protective strip
- Durable powder coat finish

Alignment-ready lift includes:

Two 7,000 lbs. rolling jacks, two carbon steel front turning radius, internal airlines, rear wheel slip plates, FLR (filter, lubricator, regulator)



Printed in the U.S.A.

Phone: 800.423.1722 Fax: 812.273.7329



www.forwardlift.com

Lit# Forward CRA14 CUTSHEET.2019.03 ©2019 Vehicle Service Group⁶⁴ All rights reserved. Unless otherwise indicated, Forward Lift, Vehicle Service Group⁶⁴, Dover and all other trademarks are property of Dover Corporation and its affiliates

LIFT OPTIONS:

- Drive-through ramps
- 3-phase motor
- Runway lighting

Forward Lifts meet the highest industry safety and performance standards. Your assurance of certification is the gold ALI/ETL certified label.



CRA14N201Y

SPECIFICATIONS	CRA14N201YBL/RD* CRA14N202YBL/RD*
Capacity	14,000 lbs. (6350kg)
Maximum Wheelbase	182-1/2" (4635mm) 215" (5461mm)
Maximum Two Wheel Alignment	166-1/4" (4225mm) 199-1/4" (5060mm)
Maximum Four Wheel Alignment	157" (3987.8mm) 172-1/4" (4375mm)
Minimum Four Wheel Alignment	88" (2235mm)
Rise	80-3/4" (2000mm)
Overall length	250" (6350mm) 283" (7188mm)
Overall width	131-3/4" (3346mm)
Width Inside Columns	116-1/4" (2953mm)
Length between Columns	195-1/4" (4959mm) 228-1/4" (5798mm)
Overall height	90-1/2" (2281mm)
Runway width	20" (508mm)
Runway Height	9" (228mm
Width Between Runways	43" (1092mm) or 46" (1168mm)
Front of Runway to Center of Radius Gauge	22-11/16" to 52-11/16" (576mm-1338mm)
Rise Time	72 seconds
Motor	2HP
Minimum Bay Size	15' x 26' (4572mm x 7925mm) 15' x 28' (4572mm x 8534mm)

*Lifts available in blue and red

Specifications subject to change without notice or liability.