

ENGINEERED TO PERFORM. BUILT TO LAST.

Reliable lift systems for independent repair shops, car dealerships, bodyshops, home enthusiasts, and heavy-duty truck facilities.



FEATURES:

Symmetrical column design 2-stage front and rear arms

Four height configuration models for most ceiling heights

15,000 lbs. Capacity

Adjustable width options

- · Cylinder rod concealed inside carriage
- Overhead cable equalization
- Single point lock release
- · Spring operated arm restraints
- Includes adapter storage bracket
- Durable powder-coated finish
- ALI certified

SPECIFICATIONS

Maximum Rise with 10"

Adapter Extensions

Overall Height

Height to Shut-Off

Overall Floor Width

Width Inside Columns

Arm Reach (Min/Max) Min. Adapter Height

Max. Adapter Height

Voltage/Amps

Drive Through Clearance

Forward Lifts meet the highest industry safety and performance standards. Your assurance of certification is the gold ALI/ETL certified label.

Capacity

DP15N000BL/RD*

15,000 lbs. (6803kg)

DP15N000 154-3/4" (3930mm)

DP15N001 175" (4445mm) DP15N002 199" (5054mm)

147-1/4" (3735mm)

154-3/8" (3921mm)

119-5/8" (3038mm) 108-1/4" (2750mm)

5-1/2" (139mm)

15-1/2" (393mm)

208V/230V, 17 amps

38" / 61" (965mm/1549mm)

83" (2120mm)



LOW-PROFILE ARM DESIGN

- Arms feature a low, 5 1/2" minimum adapter engagement height
- · Two-stage with heavy-duty reinforced gusseting
- Easily extended and retracted (61" to 38")





Printed in the U.S.A.

996 Industrial Drive Madison, IN 47250

Phone: 800.423.1722 Fax: 812.273.7329



www.forwardlift.com 📑 📵 🕡 🕞



Motor/Phase 1ph/2HP Ceiling Height Required 155-3/4" (3956mm) *Lifts available in blue and red

Specifications subject to change without notice or liability.