

DS7000N/I (SCISSORS LIFT)

SPECIFICATIONS

Lifting Capacity	3175kgs (7000lbs.)
Lifting Height (without rubber pad)	1820mm / 2010mm*
Minimum Height	189mm
Overall Width	1960mm / 1970mm*
Overall Length	4208mm / 2997mm*
Width of Platforms	530mm
Length of Platforms	1450mm / 1550mm*
Width Between Platforms	987mm / 910mm*
Motor	2.2kw
Power	3Phase, 380V, 50Hz

* for Flush Type option



FEATURES

- Controlled by dual hydraulic cylinders
- Adjustable platform extensions to adapt for vehicle length
- Platform is Electro-hydraulic operation
- Air operated safety locks
- Comes with Photo Sensor as safety Device
- Includes Rubber Pads
- Available as Surface Mounted (N) and Flush Type (I) options

HBS35A (WHEEL ALIGNMENT SCISSORS LIFT)

SPECIFICATIONS

Lifting Capacity	3500kgs (7,716 lbs.)
Lifting Height	1525mm / 1825mm*
Lowered Height	FLAT / 300mm*
Overall Length	4470mm / 5680mm*
Overall Width (max)	2283mm
Runway Length	4000mm
Runway Width	625mm
Standard Electrical Power	3 Phase, 380V, 50Hz
Compressed Air Connection	6-8 bar

* for Surface Mounted option

Rolling Jack & LED Runway Lights are optional



FEATURES

- Hydraulic system synchronizes the movement of runway and lifting platforms
- Integrated limit switches control high and low lift positions
- Easy-to-use and maintain control panel features push button controls
- Machine available as Flush Type or Surface Mounted

AUTHORISED DEALER



Rotary Lift Consolidated (Haimen) Co. Ltd.

1388, Jiangsu Xiushan Road, Haimen

Ph. : 0513 -81,261,269

E-mail : sales@rotaryliftd.com

Website : www.vsgdover.com



CAR



SEDAN



SUV



SPORTS

LCV

PICK-UP

PRO-9D PLUS (TWO POST CLEAR FLOOR)

SPECIFICATIONS

Capacity	4082kgs (9,000 lbs.)
Overall Height	3642mm
Shut-Off Height	3499mm
Minimum Ceiling Height	3658mm
Maximum Lifting Height	1930mm
Front Arm Reach	711mm - 1054mm
Rear Arm Reach	800mm - 1137mm
Overall Floor Width	3353mm
Inside Column Width	2769mm
Drive Through	2515mm
Power	3 Phase, 380V, 50Hz 1 Phase, 230V, 50Hz
Motor	2HP



FEATURES

- Padded shut-off bar to prevent damage caused by lifting a vehicle too high
- Reliable, self-setting locking system with easy to reach lock latch handle
- Powder coat finish - more durable than conventional finishes
- Symmetric 2-post lift with Asymmetric arm design provide more pickup points than ever before
- Two heavy-duty hydraulic cylinders designed to minimize down-time by requiring little maintenance
- Spring operated arm restraints, disengage at floor level
- Truck (SUV / MUV) adapters and bracket included

HPRO-9F (TWO POST BASE TYPE)

SPECIFICATIONS

Capacity	4082kgs (9,000 lbs.)
Lifting Height	2006mm
Overall Height	2819mm
Lifting Time	45 seconds
Inside Column	2819mm
Overall Floor Width	3518mm
Drive Through	2565mm
Motor	2HP
Power	3 Phase, 380V, 50Hz 1 Phase, 220V, 50Hz



FEATURES

- Commercial grade
- Powder coat finish
- Symmetric arms
- Truck (SUV / MUV) adapters included
- Base plate model

HTP40E (TWO POST CLEAR FLOOR)

SPECIFICATIONS

Lifting Capacity	4000kgs
Lifting Height	1876mm
Overall Height	3785mm
Overall Width	3152mm
Drive Through	2488mm
Front arm(shortest)	550mm
Front arm(longest)	1105mm
Rear arm(shortest)	876mm
Rear arm(longest)	1472mm
Width Between posts	2712mm
Power	3 Phase, 380V, 50Hz



FEATURES

- High pressure maintenance-free hydraulic cylinders
- Single point lock release
- Asymmetric column design
- 3 Stage arms
- Powder coat finish
- Advanced Parking Switch enabled

HF9000 / HF9000A (FOUR POST LIFT)

SPECIFICATIONS

Lifting Capacity	4082kgs (9000 lbs.)
Overall Length (with ramp)	5337mm
Overall Width (with motor)	3276mm
Width of Runways	508mm
Length of Runways	4500mm
Width Between Runways	1000mm
Inside Width of Columns	2716mm
Inside Length of Columns	4190mm
Drive-Thru Clearance	2330mm
Motor	2.2kw
Power	3Phase, 380V, 50Hz



FEATURES

- Electro-hydraulic operation
- HF9000A model includes the AK4T bolt-on alignment kit (radius gauges not included) and Rolling Jack
- Optional: Air pump for Rolling Jack (ProJack-Kit)
- Powder Coat Finish
- Available as HF9000 (Only Four Post) and HF9000A (with wheel alignment) options

HPMR 6000 (MID-RISE)

SPECIFICATIONS

Lifting Capacity	2721Kgs (6000lbs.)
Lifting Height	1368mm
Minimum Height	127mm
Overall Length	2098mm
Overall Width	1038mm
Power Options	1 Phase, 230V, 50Hz

FEATURES

- Powder coat finish
- Two hydraulic cylinders
- Safety locks at any working height with 7 locking positions
- Single point lock release
- 30 second lifting time
- Commercial grade
- Portable, easy to move
- Separate motor stand included

