Direct-Lift, PRO PARK SERIES FOUR POST LIFTS

BRO PARK 8H

Features:

- Exclusive adjustable **lock ladder leveling system** - allows your lift to be level at any height even on uneven floors
- Single point lock release
- 115 Volt operation with standard 115 volt plug provided
- Steel approach ramps included
- Durable powder coat finish

Pro Park Lifts Include:





ONE (1) JACK TRAY

FOUR (4) DRIP TRAYS



PP8H ACCESSORIES

PRO JACK 3500 1587kg. capacity sliding bridge jack

453kg. capacity each

90° POWER UNIT BRACKET

Noves power unit to front of column for additional space. Must be mounted on rear side vs. front side of PP8 column.

PRO FLOOR 8 Floor panels to fill space between runways for versatile storage needs. Requires 8 panels for full floor.



WWW.DIRECTLIFT.COM

WILL FOUR POST LIFTS FIT IN MY SHOP OR GARAGE?

Determine the space requirements needed for your four-post lift. Scan this code to watch the video or go to www.directlift and click on CEILING HEIGHT CALCULATOR.



Shown: PP8H

PP8H SPECIFICATIONS

Capacity	3628 kg
Lifting Height	2184 mm
Clearance Under Runways	1727 mm
Overall Length w/Approach Ramps	5270 mm
Overall width with motor	2921 mm
Overall width without motor	2629 mm
Overall Length without Approach Ramps	4457 mm
Approach Ramp Length	813 mm
Runway Width	470 mm
Runway Length	4305 mm
Runway Thickness	114 mm
Drive through width (Outside of tire to outside of tire)	2045 mm
Height of Columns	2070 mm
Clearance Between Columns	2388 mm
Clearance Between Runways	965 mm
Outside Runway to Outside Runway	1905 mm
Motor	115 Volt, 1HP
Shipping Weight	825 kg

Specifications subject to change without notice or liability

CONTACT THE FACTORY DIRECT WAREHOUSE IN YOUR AREA 866-347-5438

Find us on



Lit# DL_PP8H_CUTSHEET_2019

©2019 Direct-Lift[®], a Vehicle Service Group⁵⁴ brand. Printed in U.S.A., All Rights Reserved. Unless otherwiseindicated, DIRECT-LIFT, Vehicle Service Group⁵⁴, DOVER and all other trademarks are property of Dover Corporation and its affiliates.