

han1ecson[®] PRO9D Plus

9,000 LBS. CAPACITY LIFT

**CLEAR FLOOR MODEL
ASYMMETRIC ARM DESIGN
WITH SYMMETRIC POST
FOR EASE OF VEHICLE
ENTRY AND EXIT**

Padded shut-off bar to prevent damage caused by lifting a vehicle too high

Powder coat finish - more durable than conventional finishes

Symmetric 2-post lift with Asymmetric arm design provide more pickup points than ever before.


Reliable, self-setting locking system with easy to reach lock latch handle

Two heavy-duty hydraulic cylinders designed to minimize down-time by requiring little maintenance

Spring operated arm restraints, disengage at floor level

Anchor bolts included - installation requires 108mm of concrete

Adapters and bracket included



Optional screw-up truck adapters and 89mm adapter extensions available (shown with 130mm adapter)

SPECIFICATIONS PRO9D PL

Capacity	4082kg (9,000 lbs.)
Overall Height	3642mm (143-3/8")
Height to Shut-Off	3499mm (137-3/4")
Minimum Ceiling Height	3658mm (144")
Minimum Adapter Height (standard adapters)	93mm (3-5/8")
Maximum Lifting Height	1930mm (76")
Adapter Extension Heights (stack type)	45mm (1-3/4"), 130mm (5")
Front Arm Reach	(711mm - 1054mm) (28" - 41-1/2")
Rear Arm Reach	(800mm - 1137mm) (31-1/2" - 44-3/4")
Overall Floor Width	3327mm (131")
Inside Column Width	2769mm (109")
Drive Through	2515mm (99")
Voltage†	208/230v
Amps	20
Motor	2 HP

han1ecson[®]

996 Industrial Drive
Madison, Indiana 47250

866.347.5438
International sales:
812.273.5306

Specifications subject to change without notice or liability.
† single phase standard; 3-phase available at additional cost